


Advances in phase change photonics for accelerating AI

Bowei Dong

Principal Scientist


Institute of Microelectronics,
A*STAR, Singapore

dong_bowei@a-star.edu.sg



Photonics is already solving some problems, for long-range data movement and data switching. But...


Compute cluster



Optical fibres are used for long range data movement


- Optical transceivers are used for middle range data movement.
- Optical switches are used for data switching.
- **Short range data movement** (e.g. from memory to processor) and **processing** are all electronics.
- **50%** of overall energy consumption.

Compute cluster




Photonic in-memory computing is a technology that combines **in-memory computing** and **photonic computing**.

Electronic in-memory computing to **eliminate data movement from memory to processor**



Song & Kang et al., *ACS Nano.*, 17, 11994–12039 (2023)


Photonic computing for **more efficient processing**





Shastri & Tait et al., *Nature Photonics*, 15, 102-114 (2021)

Photonic in-memory computing

We use phase change materials that have two steady states at room temperature, programmed by heat pulse







Phase change photonics is the integration of phase change materials onto silicon photonics to provide non-volatile tunable functions




- Monolithic back-end-of-line integration
- A wide range of available phase change materials: amplitude and phase-only modulation

Phase change material with non-volatile tunable transmittance is used as photonic memory: direct multiplication as an example





Photonic in-memory computing uses photonic crossbar array architecture.


- Multiplication can be done by any component with tunable attenuation.
- Accumulation is done by routing rows into a common bus.



Programming phase change photonic in-memory computing chips is difficult due to fiber movement.



Computing accuracy is hard to achieve due to limited optical contrast upon programming.



20%
contrast

Original figure



Darker




Brighter






Theoretical

Experimental



Electrically programmable phase change photonic memory makes programming convenient and enlarges optical contrast.



Uniform heat flow for large area programming

✓ High optical contrast

✓ Parallel programming in one shot

High computing accuracy is achieved.

Original figure



Darker



Brighter




Theoretical



Experimental

20%
contrast



Original figure



Darker



Brighter



Theoretical



Experimental

100%
contrast

Photonic crossbar array requires multiple lasers.



On-chip MAC unit

Feldmann, Youngblood, Karpov et al., *Nature*, 589, 52-58 (2021)

To avoid interference, each row should use a different wavelength.

Number of channels
= Number of wavelengths

Limited number of wavelength
= Limited number of channels
= Limited scalability


Even worse if WDM is used.

Lasers are used as the default light source.

From lighting to LiDAR



Communication

LiDAR




DFB Laser
1973

Display




Laser
1960



Electroluminescence
1907


Lighting






Blackbody radiation
Ancient

Better coherence control



Reducing optical coherence allows one wavelength to power all channels, irrespective of the number.





Partially coherent light eliminates intensity fluctuation.



Partially coherent system can run at highspeed.






30 GHz OOK transmission



- A 9×3 photonic computing chip using electro-absorption modulators.
- 30 GHz data rate is achievable.

Partially coherent system can run CNN at 0.108 TOPS for MNIST dataset classification.



- Noise can be reduced by averaging to improve classification accuracy.



Dr Abu Sebastian



Prof Wolfram Pernice

Westfälische
Wilhelms-Universität
Münster



Prof. C. David Wright



Advanced Nanoscale Engineering Lab



Funded by the
European Union



HYBRAIN
Electronic-photonic Architectures for Brain-inspired Computing

PHOENICS



RESPITE
EIC PATHFINDER GRANT

EPSRC

Engineering and Physical Sciences
Research Council



The Science Inside

Group Spin-out



Perceived Conflict of Interest

nanoeng.materials.ox.ac.uk

Acknowledgement



Dr. Bowei Dong
Team lead



Zian Xiao
EIC/PIC Integration
NUS Ph.D. student



Dr. Haoyang Sun
Photonic computing



Dr. Jingkai Zhou
Microwave photonics



Dr. Limeng Zhang
Nonlinear activation



Dr. Tian Dong
Photonic computing

Hancheng Liu
Algorithm

Yuxiang Gao
Photonic memory
NTU FYP student

He Huang
Training optimization
NUS Master student

Mingze Sun
Nonlinear activation
NUS Master student

- Openings:
1. Photonic integrated circuits Scientist
 2. Process engineer/integration Scientist/Research engineer
 3. Student internship/exchange

Contact: dong_bowei@a-star.edu.sg